



# HP290.

### MONOBLOC AIR SOURCE HEAT PUMP



Designed for the UK climate



Low GWP R290 Refrigerant





SCOP rating

**SCOP** EFFICIENCY

364 days a year


UK customer service

Hot water in sunshine, rain, ice and snow

Temperatures up to 75'C







idealheating.com

## HP290.


The HP290 monobloc heat pump offers a low-GWP refrigerant with high efficiencies.


The HP290 can provide efficient heating and hot water throughout the year by utilising our pre-plumbed and pre-wired cylinder. The system offers our users an aesthetically pleasing heating solution with a modern design and colour when paired with Halo Lite RF, a great user experience.


Our heat pumps are supported by our industry leading customer service and warranty team which is based in the UK and is open 364-days a year, providing customer service and technical support.

### DIMENSIONS

	4.5kW & 6kW	8kW - 14kW
А	717	865
В	1299	1385
С	426	523
D	375	456
Е	121	192
F	644	656
G	379	363
Н	71	68
I	161	145
J	91	100
К	91	129







### **KEY FEATURES**



# **Technical Specification.**

		HP290 4.5kW	HP290 6kW	HP290 8kW	HP290 10kW	HP290 12kW	HP290 14kW	
Ideal Product Code		241486	241487	241488	241489	241490	241491	
MCS Certified		Yes	Yes	Yes	Yes	Yes	Yes	
Heat Pump Space Heating [35°C]*	ErP Rating	A+++	A+++	A+++	A+++	A+++	A+++	
	ηs	199	192	199	183	182	180	
	SCOP (EN14825)	5.07	4.89	5.07	4.67	4.63	4.59	
	ErP Rating	A++	A++	A++	A++	A++	A++	
Heat Pump Space Heating [55°C]*	ηs	148	149	149	141	141	139	
	SCOP (EN14825)	3.79	3.82	3.82	3.62	3.61	3.57	
	Capacity (kW)	4.5	6.2	10	12	14	15	
Heating [A 7°C / W 35°C]*	Power Input (kW)	0.87	1.27	2.13	2.5	3.11	3.41	
	СОР	5.15	4.9	4.7	4.8	4.5	4.4	
Heating [A 7°C / W 55°C]*	Capacity (kW)	4.6	6.2	9.5	12	14	15	
	Power Input (kW)	1.44	2	3.12	3.87	4.67	5.26	
	СОР	3.2	3.1	3.05	3.1	3.0	2.85	
Sound Power Level*	dB(A)	56	58	61	65	65	69	
Pipework Connection Sizes	Heating F/R	1" BSP	1" BSP	11/4" BSP	11/4" BSP	11/4" BSP	11/4" BSP	
	Width	1299	1299	1385	1385	1385	1385	
Dimensions Outdoor Unit (mm)	Depth	426	426	523	523	523	523	
	Height	717	717	865	865	865	865	
Weight (kg)	Outdoor Unit	90	90	117	135	135	135	
Electrical Data	Electrical Supply (50 Hz)	230v	230v	230v	230v	230v	230v	
	Phase	Single Phase	Single Phase	Single Phase	Single Phase	Single Phase	Single Phase	
Refrigerant Charge (kg)*	R290	0.7	0.7	1.1	1.25	1.25	1.25	
Certification	EN 14511:2018, EN 14825:2018, EN 12102-1:2022							

\*Performance data in accordance with EN 14825 : 2016, EN 1210, EN 14511 : 2018. The energy efficiency provided may not correspond to the actual energy once installed in a building, as the efficiency is influenced by other factors such as heat loss in the distribution system and the capacity of the products in relation to building size and characteristics.





#### INVESTMENT IN STATE-OF-THE ART TRAINING CENTRES

At Ideal heating our award winning 'Expert academy' offers training topics delivered both online and in-person. From comprehensive heat pump training programmes to quick toolbox tips that can be accessed via a smart phone, our Expert Academy provides a wide range of installer training options.

### **TRAINING LOCATIONS**

### OUR TRAINING CENTRES ARE ACCREDITED FOR BPEC AND CITY AND GUILDS.

Since 2012 we have invested over £10m, providing free or low-cost training to heating installers across the UK and Ireland.



### SUPPORT





Customer Service 01482 498660

Technical Help Line 01482 498663

Ideal Heating, PO Box 103, National Avenue, Kingston upon Hull, East Yorkshire, HU5 4JN

enquiries@idealheating.com

idealheating.com